



NIBE

Air/water heat pump NIBE S2125



NIBE S2125 is an intelligent inverter controlled air / water heat pump. With NIBE indoor modules, it forms a highly efficient climate system for your home. The heat pump operates with a natural refrigerant for a sustainable impact on the climate and the environment. It provides optimized savings because it automatically adapts to the home's power needs.

NIBE S2125 has an optimised annual heating factor, which provides a low operating cost and hot water with high performance. The working area provides a single-flow temperature of up to 75 °C. At an outdoor temperature of down to -25 °C, up to 65 °C is still delivered, while the sound level is low.

Together with the NIBE S-series indoor module with built-in wifi connection and the possibility of wireless accessories, it becomes a natural part of your connected home. The smart technology automatically adjusts the indoor climate and gives you complete control of the system from your smartphone or tablet. High comfort and low energy consumption - at the same time as you do nature a favour.



- **Optimized seasonal performance factor, low operating costs and high-performance hot water, using a natural refrigerant for a low environment impact.**
- **Operating range up to 75 °C supply temperature and 65 °C at -25 °C outdoor temperature.**
- **New design for low noise level.**

NIBE S2125 – part of your climate system

The NIBE S2125 is designed to be combined with a NIBE VVM indoor module or NIBE SMO control module to create a highly-efficient climate system for your home.

NIBE flexible indoor modules

NIBE VVM indoor modules provide efficient heating/cooling and hot water with high performance. They come with a smart, user-friendly control system, water heater, additional electricity and a self-regulating circulation pump. The NIBE VVM S320 and NIBE VVM 225 also include a filling valve, manometer, safety valve and expansion vessel – in other words, everything needed for a standard installation.

- **Smart control system, advanced technology, easy to understand and simple to use.**
- **Smart Energy Source for optimal integration of prioritised heat sources such as wood burners.**
- **Part of your smart home – control your comfort online using myUplink or NIBE Uplink, depending on your system.**

Choosing the right NIBE indoor module for your home

NIBE S2125	MHB 05	VVM 225	VVM 310	VVM S320	VVM S330	VVM S500
						
Compatible with	NIBE S2125-8, -12	NIBE S2125-8, -12	NIBE S2125-8, -12, -14, -16	NIBE S2125-8, -12, -14, -16	NIBE S2125-8, -12	NIBE S2125-8, -12, -14, -16
Building's output requirements, coldest day	Up to 10 kW	Up to 9 kW	Up to 14 kW	Up to 10 kW	Up to 10 kW	Up to 22 kW
Built-in electric additional heat	3 kW	9 kW	12 kW	3 x 230 V : 9 kW 1 x 230 V : 7 kW	3 x 400 V : 9 kW 1 x 230 V : 7 kW	3 x 400 V : 9 kW 1 x 230 V : 7 kW
Domestic hot water volume 40°C	–	210 l	250 l at 12 l/min	240 l	240 l	600 l at 12 l/min
Connection	Bottom	Bottom	Top	Top: NIBE VVM S320 Bottom: NIBE VVM S325	Top	Top
Height/width/depth (mm)	570/370/305	1500/600/600	1800/600/615	1800/600/615	1800/600/620	1846/760/910

Heating capacity & heating system

The NIBE S2125 is compatible with NIBE's VVM indoor modules as indicated in the table. Each NIBE VVM indoor module has a maximum recommended heating output for your climate system. When combined with a larger heat pump, the heat pump's output and energy coverage ratio, i.e. the bivalent temperature, decreases.

The NIBE VVM 310 is a two-circuit solution in which the heating system flow is independent of the flow coming from the heat pump.

The NIBE VVM 225 and VVM S320/S325 have a single-circuit system which requires the heating system's flow to be maintained above a minimum flow.

Domestic hot water

In the NIBE VVM 310 domestic hot water is heated as required in a combined pre- and post-heating coil for that reason the capacity is dependent on the flow. The NIBE VVM 225 and VVM S320/S325 have a built-in water heater with a capacity of 185 litres.

Docking




The NIBE VVM 310 enable simple and efficient docking of external heat sources to the built-in accumulator volume.

If the external heat source has a higher output and/or includes an accumulator which is larger than the accumulator volume of the NIBE VVM 310 a solution with an external accumulator tank in combination with the NIBE VVM S320/S325 is a more suitable option.

NIBE SMO control modules

The NIBE SMO control modules provide a flexible solution which is easy to customise. For solutions which include NIBE SMO, system components such as water heater, additional heat sources and other accessories are selected for the specific installation. Up to eight NIBE S2125 can be connected to a NIBE SMO 40.

Choosing the right NIBE SMO for the climate system in your home.

NIBE S2125	NIBE SMO S40	NIBE SMO 20
		
Controls	Up to eight heat pumps.	Up to one heat pump.
Self-regulating circulator pump	Available in two sizes, CPD11.	Available in two sizes, CPD11.
External heat source	Three relays for an immersion heater (up to 7 binary steps) or a boiler with shunt valve. Makes it possible to prioritise heat sources.	Three relays for immersion heater (up to 7 binary steps).
Accessories	Large range including additional climate system, pool, solar cell, heat recovery ventilation, room display etc.	Room sensor, solar cell.

Specifications NIBE S2125

		NIBE S2125-8	NIBE S2125-12	NIBE S2125-14	NIBE S2125-16	NIBE S2125-20
Product's efficiency class 35/55°C ¹⁾		A+++ / A++	A+++ / A+++			
System's efficiency class, room heating 35/55°C ²⁾		A+++ / A+++				
SCOP _{EN14825} average climate, 35/55°C		5,00 / 3,70	5,00 / 3,80	5,27 / 4,06	5,33 / 4,08	5,30 / 4,08
P _{designh} average climate 35/55°C	kW	5,33 / 5,30	6,80 / 7,60	11,00 / 11,00	11,00 / 11,00	11,00 / 11,00
SCOP _{EN14825} cold climate, 35/55°C		4,10 / 3,20	4,20 / 3,40	4,37 / 3,57	4,47 / 3,58	4,61 / 3,69
P _{designh} cold climate 35/55°C	kW	5,4/5,2	8,4 / 8,4	13,00 / 14,00	13,00 / 14,00	13,00 / 14,00
7/35 Heat capacity/COP, EN14511, nominal	kW	3,15/5,16	3,67 / 5,24	5,10 / 0,92 / 5,55	5,10 / 0,92 / 5,55	5,10 / 0,92 / 5,55
Sound level (L _{WA}), EN12102 at 7/45, nominal	dB(A)	49		55		
Rated voltage		230 V – 50 Hz / 400 V 3N – 50 Hz		400 V 3N – 50 Hz	230 V – 50 Hz / 400 V 3N – 50 Hz	
CO ₂ - equivalent (hermetically sealed refrigerant circuit) ³⁾	tonnes	0,0024		0,00345		
Height/width/depth	mm	1070 / 1130 / 820		1180 / 1278 / 831		
Weight (excluding packaging)	kg	179		215		


¹⁾ Scale for product's efficiency class, room heating A+++ – D. ²⁾ Scale for system's efficiency class, room heating. A+++ – G. Reported system efficiency takes the product's temperature regulator into account. ³⁾ The NIBE S2125 does not require annual inspection in accordance with the F-Gas Regulation.

M13616 CILEN NIBE S2125 2527-1
Subject to printing errors and changes. ©NIBE 2025


Sustainable energy solutions

Since 1952, NIBE has been manufacturing energy-efficient and sustainable climate solutions for your home. It all started in Markaryd in Sweden and we value our Nordic heritage by harnessing the power of nature. We combine renewable energy with smart technology in order to offer effective solutions so that together we can build a more sustainable future.




Whether it's a chilly winter's day or a hot summer's afternoon, we need a well-balanced indoor climate for a comfortable everyday life, whatever the weather. Our wide range of products supplies your home with cooling, heating, ventilation and hot water, so that you can create a pleasant indoor climate with a low impact on nature.



System's efficiency for room heating, 35°C



System's efficiency for room heating, 55°C.

Product's efficiency class and load profile for hot water with NIBE VVM 310/VVM 320/VVM 325.

NIBE Energy Systems
BOX 14, 285 21 Markaryd
Tel. 0433-27 30 00 | nibe.se

NIBE