



ENERG Y (JA) ehepгия · ενεργεια (Ε) (ΙΑ)



AMS20-10 + SHB20-12



























A

В

C

D

E

F

G



2015

Supplier's name:	NIBE AB		
Model:	NIBE AMS 20-10 + SHB 20-12		
Temperature application	35	55	°C
Declared load profile for water			
heating			
Seasonal space heating energy	A +++	A++	
efficiency class, average climate:	Аттт	ATT	
Water heating energy efficiency			
class, average climate:			
Detect be at a struct as a second alimenta.	6	6	kW
Rated heat output, average climate:			
Annual energy consumption for	2834	3961	kWh
space heating, average climate			
Annual electricity consumption for			kWh
water heating, average climate Seasonal space heating energy		1	
	181	132	%
efficiency, average climate: Water heating energy efficiency,			
average climate:			%
Sound power level LWA indoors	3.	5	dB
Rated heat output, cold climate:	7	6	kW
Rated heat output, warm climate:	7	7	kW
Annual energy consumption for	1		
space heating, cold climate	4059	5204	kWh
Annual electricity consumption for			
water heating, cold climate			kWh
Annual energy consumption for			
space heating, warm climate	1379	1964	kWh
Annual electricity consumption for			kWh
water heating, warm climate			KVVII
Seasonal space heating energy	155	114	%
efficiency, cold climate:	100	114	70
Water heating energy efficiency, cold			%
climate:		-	70
Seasonal space heating energy	260	177	%
efficiency, warm climate:	200		70
Water heating energy efficiency,			%
warm climate:			
Sound power level LWA outdoors	5	4	dB

Data for package fiche

Controller class	CLASS VI		
Controler contribution to efficiency	4,0		%
Seasonal space heating energy			
efficiency of package, average	185	136	%
climate:			
Seasonal space heating energy	_	_	
efficiency class for package, average	A +++	A++	%
climate:			
Seasonal space heating energy efficiency of package, cold climate:	159	118	%
Seasonal space heating energy efficiency of package, warm climate:	264	181	%

Doc. Number_Compliance file: DOC_0004873

Model(s):	NIBE AMS 20-10 + SHB 20-12			
Type of heat source/sink:	Air/water			
Low-temperature heat pump:	No			
Equipped with supplementary heater:	Yes			
Heat pump combination heater:	No			
Climate condition:	Average			
Temperature application:	Medium temperature (55 °C)			
Applied standards: EN 14825:2022, EN 12102-1:2022				
	Seasonal space heating			



Applied standards: EN 14825:2022, EN 12	102-1:2022						
Rated heat output	Prated	6,5	kW	Seasonal space heating energy efficiency	η_s	132	%
Declared capacity for part load at outdoor tem	perature Tj			Declared coefficient of performance for par	t load at outdo	or temperatu	re Tj
Tj = -7 °C	Pdh	5,8	kW	Tj = -7 °C	COPd	1,98	
Tj = +2 °C	Pdh	3,5	kW	Tj = +2 °C	COPd	3,17	
Tj = +7 °C	Pdh	2,3	kW	Tj = +7 °C	COPd	4,98	
Tj = +12 °C	Pdh	2,2	kW	Tj = +12 °C	COPd	5,50	
Tj = biv	Pdh	5,8	kW	Tj = biv	COPd	1,98	
Tj = TOL	Pdh	5,8	kW	Tj = TOL	COPd	1,69	
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °C)	COPd		
Bivalent temperature	T _{biv}	-7	°C	Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcych		kW	Cycling interval efficiency	COPcyc		-
Degradation co-efficient	Cdh	0,98	-	Heating water operating limit	WTOL	60	°C
Power consumption in modes other than active mode Off mode Poes 0,003 kW		Supplementary heater Rated heat output	Psup	0,7	kW		
	P _{OFF}		+	Rated heat output	Psup	0,7	KVV
Thermostat-off mode	P _{TO}	0,008	kW		1		
Standby mode	P_{SB}	0,008	kW	Type of energy input	Electric		
Crankcase heater mode	P _{CK}	0,000	kW				
Other items							
Capacity control		Variable		Rated air flow rate, outdoors		3000	m³/h
				Rated water flow rate, indoor heat			2.0
Sound power level, indoors/outdoors	L _{WA}	35/54	dB	exchanger			m³/h
Annual energy consumption	Q_{HF}	3961	kWh	Rated brine or water flow rate, outdoor heat exchanger			m³/h
	=		<u>. </u>	<u> </u>			1
For heat pump combination heater:	1		1	I	1 _ 1		1
Declared load profile				Water heating energy efficiency	η_{wh}		%
Daily electricity consumption	Q _{elec}		kWh	Daily fuel consumption	Q_{fuel}		kWh
Annual electricity consumption	AEC		kWh	Annual fuel consumption	AFC		GJ
Contact details	© NIBF F	nergy Syste	ems - Box	14 - Hannabadsvägen 5 - 28521 Mark	arvd - Swe	den	

Document number_Compliance file:

DOC_0004873