



ENERGY


NIBE

NIBE F1345-40



55 °C

35 °C



A++

A+++



47 dB



dB

■ 46
■ **46**
■ 46
46
kW

■ 46
■ **46**
■ 46
46
kW



2019

811/2013



ENERGY

NIBE

NIBE F1345-40



A⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺⁺

A⁺

A

B

C


D

E

F

G

+



+



+



+



Supplier's name:	NIBE		
Model:	NIBE F1345-40		
Temperature application	35	55	°C
Declared load profile for water heating			
Seasonal space heating energy efficiency class, average climate:	A+++	A++	
Water heating energy efficiency class, average climate:			
Rated heat output, average climate:	46	46	kW
Annual energy consumption for space heating, average climate	19996	25093	kWh
Annual electricity consumption for water heating, average climate			kWh
Seasonal space heating energy efficiency, average climate:	182	143	%
Water heating energy efficiency, average climate:			%
Sound power level LWA indoors	47		dB
Rated heat output, cold climate:	46	46	kW
Rated heat output, warm climate:	46	46	kW
Annual energy consumption for space heating, cold climate	22939	28857	kWh
Annual electricity consumption for water heating, cold climate			kWh
Annual energy consumption for space heating, warm climate	12931	16202	kWh
Annual electricity consumption for water heating, warm climate			kWh
Seasonal space heating energy efficiency, cold climate:	190	149	%
Water heating energy efficiency, cold climate:			%
Seasonal space heating energy efficiency, warm climate:	182	144	%
Water heating energy efficiency, warm climate:			%
Sound power level LWA outdoors	-		dB

Data for package fiche

Controller class	II		
Controller contribution to efficiency	2		%
Seasonal space heating energy efficiency of package, average climate:	184	145	%
Seasonal space heating energy efficiency class for package, average climate:	A+++	A++	%
Seasonal space heating energy efficiency of package, cold climate:	192	151	%
Seasonal space heating energy efficiency of package, warm climate:	184	146	%

Model(s):		NIBE F1345-40		NIBE						
Type of heat source/sink:		Brine-to-water								
Low-temperature heat pump:		No								
Equipped with supplementary heater:		No								
Heat pump combination heater:		No								
Climate condition:		Average								
Temperature application:		Medium temperature (55 °C)								
Applied standards: EN14825										
Rated heat output		Prated	46,0	kW	Seasonal space heating energy efficiency		η_s	143	%	
<i>Declared capacity for part load at outdoor temperature Tj</i>				<i>Declared coefficient of performance for part load at outdoor temperature Tj</i>						
Tj = -7 °C	Pdh	38,2	kW	Tj = -7 °C	COPd	3,33	-			
Tj = +2 °C	Pdh	39,1	kW	Tj = +2 °C	COPd	3,79	-			
Tj = +7 °C	Pdh	19,9	kW	Tj = +7 °C	COPd	4,21	-			
Tj = +12 °C	Pdh	20,1	kW	Tj = +12 °C	COPd	4,51	-			
Tj = biv	Pdh	38,4	kW	Tj = biv	COPd	3,41	-			
Tj = TOL	Pdh	37,8	kW	Tj = TOL	COPd	3,19	-			
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °C)	COPd		-			
Bivalent temperature				T _{biv}	-5,7	°C	Operation limit temperature			
Cycling interval capacity for heating				P _{cyh}		kW	Cycling interval efficiency		COP _{cyh}	
Degradation co-efficient				Cdh	0,99	-	Heating water operating limit		WTOL	65
<i>Power consumption in modes other than active mode</i>				<i>Supplementary heater</i>						
Off mode	P _{OFF}	0,002	kW	Rated heat output		P _{sup}	8,2	kW		
Thermostat-off mode	P _{TO}	0,05	kW							
Standby mode	P _{SB}	0,007	kW	Type of energy input		Electric				
Crankcase heater mode	P _{CK}	0,08	kW							
<i>Other items</i>										
Capacity control		variable		Rated air flow rate, outdoors					m ³ /h	
Sound power level, indoors/outdoors		L _{WA}	47/-	dB	Rated water flow rate, indoor heat exchanger			4,07	m ³ /h	
Annual energy consumption		Q _{HE}	25093	kWh	Rated brine or water flow rate, outdoor heat exchanger			7,77	m ³ /h	
<i>For heat pump combination heater:</i>										
Declared load profile				Water heating energy efficiency		η_{wh}			%	
Daily electricity consumption				Q _{elec}		kWh	Daily fuel consumption		Q _{fuel}	
Annual electricity consumption				AEC		kWh	Annual fuel consumption		AFC	
Approved by:										
Contact details		© NIBE Energy Systems - Box 14 - Hannabadsvägen 5 - 28521 Markaryd - Sweden								