



## IJA ENERG енергия · ενεργεια



NIBE F1345-40

























B

2015

811/2013

Supplier's name:	NI			
Model:	NIBE F			
Temperature application	35	55	°C	
Declared load profile for water				
heating		ĭ		
Seasonal space heating energy	A+++	A++		
efficiency class, average climate:		7		
Water heating energy efficiency				
class, average climate:		ı		
Rated heat output, average climate:	46	46	kW	
Annual energy consumption for	19996	25093	kWh	
space heating, average climate		20000		
Annual electricity consumption for			kWh	
water heating, average climate		1		
Seasonal space heating energy	182	143	%	
efficiency, average climate:				
Water heating energy efficiency,			%	
average climate:		17	-ID	
Sound power level LWA indoors		17 1	dB	
Rated heat output, cold climate:	46	46	kW	
Rated heat output, warm climate:	46	46	kW	
Annual energy consumption for	22939	28857	kWh	
space heating, cold climate		20007		
Annual electricity consumption for water heating, cold climate			kWh	
Annual energy consumption for				
space heating, warm climate	12931	16202	kWh	
Annual electricity consumption for				
water heating, warm climate			kWh	
Seasonal space heating energy	100	140	0/	
efficiency, cold climate:	190	149	%	
Water heating energy efficiency, cold			%	
climate:			70	
Seasonal space heating energy	182	144	%	
efficiency, warm climate:	102		/	
Water heating energy efficiency,			%	
warm climate:				
Sound power level LWA outdoors		-	dB	

## Data for package fiche

Controller class			
Controler contribution to efficiency	2		%
Seasonal space heating energy efficiency of package, average climate:	184	145	%
Seasonal space heating energy efficiency class for package, average climate:	A+++	A++	%
Seasonal space heating energy efficiency of package, cold climate:	192	151	%
Seasonal space heating energy efficiency of package, warm climate:	184	146	%

Model(s):			NII	BE F1345-40
Type of heat source/sink:			Bri	ine-to-water
Low-temperature heat pump:				No
Equipped with supplementary heater	:			No
Heat pump combination heater:				No
Climate condition:				Average
emperature application:		Medium temperature (55 °C)		
Applied standards: EN14825				
Rated heat output	Prated	46 O	k\\\	Seasonal space heating e



, -	Prated  perature Tj Pdh	38,2 39,1 19,9 20,1 38,4 37,8	kW kW kW kW kW kW kW	Seasonal space heating energy efficiency  Declared coefficient of performance for part  Tj = -7 °C  Tj = +2 °C  Tj = +7 °C  Tj = +12 °C  Tj = biv  Tj = TOL  Tj = -15 °C (if TOL < -20 °C)  Operation limit temperature	ns rt load at outdo COPd COPd COPd COPd COPd COPd COPd COPd	3,33 3,79 4,21 4,51 3,41 3,19	% re Tj
Declared capacity for part load at outdoor tem  Tj = -7 °C  Tj = +2 °C  Tj = +7 °C  Tj = +12 °C  Tj = biv  Tj = TOL  Tj = -15 °C (if TOL < -20 °C)  Bivalent temperature	Perature Tj Pdh	38,2 39,1 19,9 20,1 38,4 37,8	kW kW kW kW kW	efficiency  Declared coefficient of performance for part  Tj = -7 °C  Tj = +2 °C  Tj = +7 °C  Tj = +12 °C  Tj = biv  Tj = TOL  Tj = -15 °C (if TOL < -20 °C)  Operation limit temperature	COPd COPd COPd COPd COPd COPd COPd COPd	3,33 3,79 4,21 4,51 3,41 3,19	re Tj
Declared capacity for part load at outdoor tem  Tj = -7 °C  Tj = +2 °C  Tj = +7 °C  Tj = +12 °C  Tj = biv  Tj = TOL  Tj = -15 °C (if TOL < -20 °C)  Bivalent temperature	Perature Tj Pdh	38,2 39,1 19,9 20,1 38,4 37,8	kW kW kW kW kW	Declared coefficient of performance for partial Tj = -7 °C Tj = +2 °C Tj = +7 °C Tj = +12 °C Tj = biv Tj = TOL Tj = -15 °C (if TOL < -20 °C)  Operation limit temperature	COPd COPd COPd COPd COPd COPd COPd COPd	3,33 3,79 4,21 4,51 3,41 3,19	re Tj
Tj = -7 °C  Tj = +2 °C  Tj = +7 °C  Tj = +7 °C  Tj = +12 °C  Tj = biv  Tj = TOL  Tj = -15 °C (if TOL < -20 °C)  Bivalent temperature	Pdh	39,1 19,9 20,1 38,4 37,8	kW kW kW kW kW	Tj = -7 °C  Tj = +2 °C  Tj = +7 °C  Tj = +12 °C  Tj = biv  Tj = TOL  Tj = -15 °C (if TOL < -20 °C)  Operation limit temperature	COPd COPd COPd COPd COPd COPd COPd COPd	3,33 3,79 4,21 4,51 3,41 3,19	-
Tj = -7 °C  Tj = +2 °C  Tj = +7 °C  Tj = +7 °C  Tj = +12 °C  Tj = biv  Tj = TOL  Tj = -15 °C (if TOL < -20 °C)  Bivalent temperature	Pdh	39,1 19,9 20,1 38,4 37,8	kW kW kW kW kW	Tj = -7 °C  Tj = +2 °C  Tj = +7 °C  Tj = +12 °C  Tj = biv  Tj = TOL  Tj = -15 °C (if TOL < -20 °C)  Operation limit temperature	COPd COPd COPd COPd COPd COPd COPd COPd	3,33 3,79 4,21 4,51 3,41 3,19	-
Tj = +2 °C Tj = +7 °C Tj = +12 °C Tj = biv Tj = TOL Tj = -15 °C (if TOL < -20 °C)  Bivalent temperature	Pdh Pdh Pdh Pdh Pdh Pdh Pdh Pdh Pdh Pch	39,1 19,9 20,1 38,4 37,8	kW kW kW kW kW	Tj = +2 °C Tj = +7 °C Tj = +12 °C Tj = biv Tj = TOL Tj = -15 °C (if TOL < -20 °C)  Operation limit temperature	COPd COPd COPd COPd COPd COPd	3,79 4,21 4,51 3,41 3,19	-
Tj = +7 °C Tj = +12 °C Tj = biv Tj = TOL Tj = -15 °C (if TOL < -20 °C)  Bivalent temperature	Pdh Pdh Pdh Pdh Pdh Pcych	19,9 20,1 38,4 37,8	kW kW kW c°C	Tj = +7 °C Tj = +12 °C Tj = biv Tj = TOL Tj = -15 °C (if TOL < -20 °C)  Operation limit temperature	COPd COPd COPd COPd	4,21 4,51 3,41 3,19	
Tj = biv Tj = TOL Tj = -15 °C (if TOL < -20 °C) Bivalent temperature	Pdh Pdh Pdh T <sub>biv</sub> Pcych	38,4 37,8 -5,7	kW kW kW	Tj = biv Tj = TOL Tj = -15 °C (if TOL < -20 °C)  Operation limit temperature	COPd COPd COPd	3,41 3,19	- - - -
Tj = TOL Tj = -15 °C (if TOL < -20 °C) Bivalent temperature	Pdh Pdh  T <sub>biv</sub> Pcych	-5,7	kW kW	Tj = TOL Tj = -15 °C (if TOL < -20 °C)  Operation limit temperature	COPd COPd	3,19	
Tj = -15 °C (if TOL < -20 °C)  Bivalent temperature	Pdh  T <sub>biv</sub> Pcych	-5,7	kW °C	Tj = -15 °C (if TOL < -20 °C)  Operation limit temperature	COPd	,	<u>-</u>
Bivalent temperature	T <sub>biv</sub>	,	°C	Operation limit temperature		10	
•	Pcych	,			TOL	10	
•	Pcych	,			TOL		
Cycling interval capacity for heating		0.00	kW I			-10	°C
	Cdh	n aa	+	Cycling interval efficiency	COPcyc		<u> </u>
Degradation co-efficient		0,55	-	Heating water operating limit	WTOL	65	°C
Power consumption in modes other than active	e mode			Supplementary heater			
Off mode	P <sub>OFF</sub>	0,002	kW	Rated heat output	Psup	8,2	kW
Thermostat-off mode	P <sub>TO</sub>	0,05	kW				•
Standby mode	P <sub>SB</sub>	0,007	kW	Type of energy input		Electric	
Crankcase heater mode	P <sub>CK</sub>	0,08	kW				
Other items							
Capacity control		variable		Rated air flow rate, outdoors			m³/h
				Rated water flow rate, indoor heat			
Sound power level, indoors/outdoors	$L_WA$	47/-	dB	exchanger		4,07	m³/h
				Rated brine or water flow rate,			
Annual energy consumption	$Q_{HE}$	25093	kWh	outdoor heat exchanger		7,77	m³/h
For heat pump combination heater:							
Declared load profile				Water heating energy efficiency	$\eta_{wh}$		%
Daily electricity consumption	Q <sub>elec</sub>		kWh	Daily fuel consumption	$Q_{fuel}$		kWh
Annual electricity consumption	AEC		kWh	Annual fuel consumption	AFC		GJ
Approved by:							·
Contact details	© NIBE Energy Systems - Box 14 - Hannabadsvägen 5 - 28521 Markaryd - Sweden						