



ENERG Υ UA EHEPΓИЯ · ενεργεια ΙΕ ΙΑ

NIBE

NIBE F1355-43

































A

A

B

C

D

E

J

G



811/2013

2015

Supplier's name:	NIBE		
Model:	NIBE F1		
Temperature application	35	55	°C
Declared load profile for water			
heating			
Seasonal space heating energy	۸	Λ	
efficiency class, average climate:	A+++	A+++	
Water heating energy efficiency			
class, average climate:			
Rated heat output, average climate:	45	42	kW
Annual energy consumption for	18588	21700	kWh
space heating, average climate	10000	21700	KVVII
Annual electricity consumption for			Id\A/b
water heating, average climate			kWh
Seasonal space heating energy	192	152	%
efficiency, average climate:	192	152	%
Water heating energy efficiency,			%
average climate:			%
Sound power level LWA indoors	47		dB
Rated heat output, cold climate:	45	42	kW
Rated heat output, warm climate:	45	42	kW
Annual energy consumption for	21011	24977	kWh
space heating, cold climate	21011	24977	KVVII
Annual electricity consumption for			kWh
water heating, cold climate			KVVII
Annual energy consumption for	11463	13776	kWh
space heating, warm climate	11403	13/70	KVVII
Annual electricity consumption for			kWh
water heating, warm climate			KVVII
Seasonal space heating energy	203	158	%
efficiency, cold climate:	203	130	70
Water heating energy efficiency, cold			0/
climate:			%
Seasonal space heating energy	202	155	%
efficiency, warm climate:	202	100	70
Water heating energy efficiency,			%
warm climate:			70
Sound power level LWA outdoors	-		dB

Data for package fiche

Controller class			
Controler contribution to efficiency	2		%
Seasonal space heating energy efficiency of package, average climate:	194	154	%
Seasonal space heating energy efficiency class for package, average climate:	A+++	A+++	%
Seasonal space heating energy efficiency of package, cold climate:	205	160	%
Seasonal space heating energy efficiency of package, warm climate:	204	157	%

Model(s):	NIBE F1355-43		
Type of heat source/sink:	Brine/water		
Low-temperature heat pump:	No		
Equipped with supplementary heater:	No		
Heat pump combination heater:	No		
Climate condition:	Average		
Temperature application:	Medium temperature (55 °C)		
Applied standards: EN14825 - EN12102-1			



Temperature application:			Medium te	emperature (55 °C)			
Applied standards: EN14825 - EN12102	-1						
Rated heat output	Prated	42,0	kW	Seasonal space heating energy efficiency	η _s	152	%
Declared capacity for part load at outdoor tem	perature Ti			Declared coefficient of performance for par	t load at outdo	or temperatu	re Ti
Tj = -7 °C	Pdh	36,5	kW	Tj = -7 °C	COPd	3,1	
Tj = +2 °C	Pdh	26,6	kW	Tj = +2 °C	COPd	3,9	
Tj = +7 °C	Pdh	13,3	kW	Tj = +7 °C	COPd	4,7	
Tj = +12 °C	Pdh	7,8	kW	Tj = +12 °C	COPd	5,4	
Tj = biv	Pdh	40,1	kW	Tj = biv	COPd	2,8	
Tj = TOL	Pdh	40,1	kW	Tj = TOL	COPd	2,8	
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °C)	COPd		
Bivalent temperature	T _{biv}	-10	°C	Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcych		kW	Cycling interval efficiency	COPcyc		-
Degradation co-efficient	Cdh	1,00	-	Heating water operating limit	WTOL	65	°C
Power consumption in modes other than active Off mode	P _{OFF}	0,008	kW	Supplementary heater Rated heat output	Psup	0,0	kW
Thermostat-off mode	P _{TO}	0	kW				
Standby mode	P _{SB}	0,008	kW	Type of energy input	Electric		
Crankcase heater mode	P _{CK}	0,02	kW				
Other items							
Capacity control		Variable		Rated air flow rate, outdoors			m³/h
				Rated water flow rate, indoor heat			
Sound power level, indoors/outdoors	L_WA	47/-	dB	exchanger			m³/h
				Rated brine or water flow rate,			
Annual energy consumption	Q_{HE}	21700	kWh	outdoor heat exchanger		5,92	m³/h
For heat pump combination heater:							
Declared load profile				Water heating energy efficiency	η_{wh}		%
Daily electricity consumption	Q _{elec}		kWh	Daily fuel consumption	Q_{fuel}		kWh
Annual electricity consumption	AEC		kWh	Annual fuel consumption	AFC		GJ
Approved by:				·	<u> </u>		
Contact details	© NIBE E	nergy Syste	ems - Box	14 - Hannabadsvägen 5 - 28521 Mark	arvd - Swed	den	
		- 61 - 1000			. ,		