




**ENERG**  
енергия · ενεργεια




**NIBE**

NIBE S1256-13



55 °C

35 °C



**39** dB



dB

■ 11  
■ **11**  
■ 11  
kW

■ 11  
■ **11**  
■ 11  
kW



2019

811/2013





**ENERG**  
енергия · ενέργεια


Y IJA  
IE IA

**NIBE**



NIBE S1256-13



A+++



A+



2019

811/2013



# ENERG

енергия · ενέργεια

Y






IJA


IE


IA


## NIBE


## NIBE S1256-13













+ 

+ 

+ 

+ 

Supplier's name:	NIBE AB		
Model:	NIBE S1256-13		
Temperature application	35	55	°C
Declared load profile for water heating	XL		
Seasonal space heating energy efficiency class, average climate:	<b>A+++</b>	<b>A+++</b>	
Water heating energy efficiency class, average climate:	<b>A+</b>		
Rated heat output, average climate:	11	11	kW
Annual energy consumption for space heating, average climate	3868	5303	kWh
Annual electricity consumption for water heating, average climate	1325		kWh
Seasonal space heating energy efficiency, average climate:	227	163	%
Water heating energy efficiency, average climate:	126		%
Sound power level LWA indoors	39		dB
Rated heat output, cold climate:	11	11	kW
Rated heat output, warm climate:	11	11	kW
Annual energy consumption for space heating, cold climate	4423	6081	kWh
Annual electricity consumption for water heating, cold climate	1325		kWh
Annual energy consumption for space heating, warm climate	2512	3413	kWh
Annual electricity consumption for water heating, warm climate	1325		kWh
Seasonal space heating energy efficiency, cold climate:	237	170	%
Water heating energy efficiency, cold climate:	126		%
Seasonal space heating energy efficiency, warm climate:	226	164	%
Water heating energy efficiency, warm climate:	126		%
Sound power level LWA outdoors			dB

**Data for package fiche with SMO or VVM**

Controller class	CLASS VI		
Controller contribution to efficiency	4,0		%
Seasonal space heating energy efficiency of package, average climate:	231	167	%
Seasonal space heating energy efficiency class for package, average climate:	<b>A+++</b>	<b>A+++</b>	%
Seasonal space heating energy efficiency of package, cold climate:	241	174	%
Seasonal space heating energy efficiency of package, warm climate:	230	168	%

<b>Model(s):</b>		<b>NIBE S1256-13</b>		<b>NIBE</b>						
Type of heat source/sink:		Brine/water								
Low-temperature heat pump:		No								
Equipped with supplementary heater:		Yes								
Heat pump combination heater:		Yes								
Climate condition:		Average								
Temperature application:		Medium temperature (55 °C)								
Applied standards: EN14825 - EN16147 - EN12102-1										
<b>Rated heat output</b>		Prated	11,0	kW	<b>Seasonal space heating energy efficiency</b>		$\eta_s$	163	%	
<i>Declared capacity for part load at outdoor temperature Tj</i>				<i>Declared coefficient of performance for part load at outdoor temperature Tj</i>						
Tj = -7 °C	Pdh	9,7	kW	Tj = -7 °C	COPd	3,34				
Tj = +2 °C	Pdh	6,0	kW	Tj = +2 °C	COPd	4,24				
Tj = +7 °C	Pdh	3,8	kW	Tj = +7 °C	COPd	5,01				
Tj = +12 °C	Pdh	2,5	kW	Tj = +12 °C	COPd	5,33				
Tj = biv	Pdh	11,0	kW	Tj = biv	COPd	3,09				
Tj = TOL	Pdh	11,0	kW	Tj = TOL	COPd	3,09				
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °C)	COPd					
Bivalent temperature				T <sub>biv</sub>	-10	°C	Operation limit temperature			
Cycling interval capacity for heating				P <sub>cyh</sub>		kW	Cycling interval efficiency		COP <sub>cyh</sub>	-
Degradation co-efficient				Cdh	0,99	-	Heating water operating limit		WTOL	65 °C
<i>Power consumption in modes other than active mode</i>				<i>Supplementary heater</i>						
Off mode	P <sub>OFF</sub>	0,004	kW	Rated heat output		P <sub>sup</sub>	0,0	kW		
Thermostat-off mode	P <sub>TO</sub>	0,007	kW							
Standby mode	P <sub>SB</sub>	0,010	kW	Type of energy input		Electric				
Crankcase heater mode	P <sub>CK</sub>	0,008	kW							
<i>Other items</i>										
Capacity control	Variable			Rated air flow rate, outdoors					m <sup>3</sup> /h	
Sound power level, indoors/outdoors	L <sub>WA</sub>	39/-	dB	Rated water flow rate, indoor heat exchanger					m <sup>3</sup> /h	
Annual energy consumption	Q <sub>HE</sub>	5303	kWh	Rated brine or water flow rate, outdoor heat exchanger			2,20		m <sup>3</sup> /h	
<i>For heat pump combination heater:</i>										
<b>Declared load profile</b>		<b>XL</b>		<b>Water heating energy efficiency</b>		$\eta_{wh}$	126	%		
Daily electricity consumption	Q <sub>elec</sub>	6,294	kWh	Daily fuel consumption		Q <sub>fuel</sub>		kWh		
Annual electricity consumption	AEC	1325	kWh	Annual fuel consumption		AFC		GJ		
<b>Contact details</b>		© NIBE Energy Systems - Box 14 - Hannabadsvägen 5 - 28521 Markaryd - Sweden								