



ENERG
енергия · ενέργεια




NIBE S2125-20



55 °C

35 °C



A+++

A+++



dB



55 dB

■ 14
■ **11**
■ 13
kW

■ 13
■ **11**
■ 13
kW



2019

811/2013



ENERG

енергия · ενεργεια

Y

IJA

IE

IA

 **NIBE**

NIBE S2125-20 + SMO



A⁺⁺⁺

A⁺⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺

A

B

C


D

E

F

G

+



+



+




+



Supplier's name:	NIBE AB		
Model:	NIBE S2125-20		
Temperature application	35	55	°C
Declared load profile for water heating			
Seasonal space heating energy efficiency class, average climate:	A+++	A+++	
Water heating energy efficiency class, average climate:			
Rated heat output, average climate:	11,0	11,0	kW
Annual energy consumption for space heating, average climate	4288	5571	kWh
Annual electricity consumption for water heating, average climate			kWh
Seasonal space heating energy efficiency, average climate:	209	160	%
Water heating energy efficiency, average climate:			%
Sound power level LWA indoors			dB
Rated heat output, cold climate:	13,0	14,0	kW
Rated heat output, warm climate:	13,0	13,0	kW
Annual energy consumption for space heating, cold climate	6960	9361	kWh
Annual electricity consumption for water heating, cold climate			kWh
Annual energy consumption for space heating, warm climate	2759	3631	kWh
Annual electricity consumption for water heating, warm climate			kWh
Seasonal space heating energy efficiency, cold climate:	181	144	%
Water heating energy efficiency, cold climate:			%
Seasonal space heating energy efficiency, warm climate:	249	188	%
Water heating energy efficiency, warm climate:			%
Sound power level LWA outdoors	55		dB

Data for package fiche SMO

Controller class	CLASS VI		
Controller contribution to efficiency	4,0		%
Seasonal space heating energy efficiency of package, average climate:	213	164	%
Seasonal space heating energy efficiency class for package, average climate:	A+++	A+++	%
Seasonal space heating energy efficiency of package, cold climate:	185	148	%
Seasonal space heating energy efficiency of package, warm climate:	253	192	%

Model(s):				NIBE S2125-20							
Type of heat source/sink:				Air/water							
Low-temperature heat pump:				No							
Equipped with supplementary heater:				No							
Heat pump combination heater:				No							
Climate condition:				Average							
Temperature application:				Medium temperature (55 °C)							
Applied standards: EN 14825:2022, EN 12102-1:2022											
Rated heat output			Prated	11,0	kW	Seasonal space heating energy efficiency			ηs	160	%
Declared capacity for part load at outdoor temperature Tj						Declared coefficient of performance for part load at outdoor temperature Tj					
Tj = -7 °C	Pdh	9,6	kW	Tj = -7 °C			COPd	2,49			
Tj = +2 °C	Pdh	5,8	kW	Tj = +2 °C			COPd	4,07			
Tj = +7 °C	Pdh	5,1	kW	Tj = +7 °C			COPd	5,25			
Tj = +12 °C	Pdh	5,7	kW	Tj = +12 °C			COPd	6,25			
Tj = biv	Pdh	10,5	kW	Tj = biv			COPd	2,16			
Tj = TOL	Pdh	10,5	kW	Tj = TOL			COPd	2,16			
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °C)			COPd				
Bivalent temperature		Tbiv	-10	°C	Operation limit temperature			TOL	-10	°C	
Cycling interval capacity for heating		Pcych		kW	Cycling interval efficiency			COPcyc		-	
Degradation co-efficient		Cdh	0,98	-	Heating water operating limit			WTOL	65	°C	
Power consumption in modes other than active mode						Supplementary heater					
Off mode	P _{OFF}	0,007	kW	Rated heat output			Psup	0,0	kW		
Thermostat-off mode	P _{TO}	0,014	kW								
Standby mode	P _{SB}	0,010	kW	Type of energy input			Electric				
Crankcase heater mode	P _{CK}	0,011	kW								
Other items											
Capacity control		Variable		Rated air flow rate, outdoors				2900	m³/h		
Sound power level, indoors/outdoors		L _{WA}	-/55	dB	Rated water flow rate, indoor heat exchanger					m³/h	
Annual energy consumption		Q _{HE}	5571	kWh	Rated brine or water flow rate, outdoor heat exchanger					m³/h	
For heat pump combination heater:											
Declared load profile					Water heating energy efficiency			η _{wh}		%	
Daily electricity consumption		Q _{elec}		kWh	Daily fuel consumption			Q _{fuel}		kWh	
Annual electricity consumption		AEC		kWh	Annual fuel consumption			AFC		GJ	
Contact details		© NIBE Energy Systems - Box 14 - Hannabadsvägen 5 - 28521 Markaryd - Sweden									