



**ENERG**  
енергия · ενέργεια




**NIBE**

AMS 10-8 + SHB10-12



55 °C

35 °C



**A++**

**A++**



**31** dB



**52** dB

■ 10  
■ 7  
■ 8  
kW

■ 9  
■ 7  
■ 8  
kW



2019

811/2013



# ENERG

енергия · ενεργεια

Y

IJA

IE

IA

**NIBE**

AMS10-8 + SHB10-12



A<sup>++</sup>

A<sup>+++</sup>

A<sup>++</sup>

A<sup>++</sup>

A<sup>+</sup>

A

B

C


D

E

F

G

+



+



+



+



Supplier's name:	NIBE AB		
Model:	NIBE AMS 10-8 + SHB 10-12		
Temperature application	35	55	°C
Declared load profile for water heating			
Seasonal space heating energy efficiency class, average climate:	<b>A++</b>	<b>A++</b>	
Water heating energy efficiency class, average climate:			
Rated heat output, average climate:	7	7	kW
Annual energy consumption for space heating, average climate	3622	4486	kWh
Annual electricity consumption for water heating, average climate			kWh
Seasonal space heating energy efficiency, average climate:	152	126	%
Water heating energy efficiency, average climate:			%
Sound power level LWA indoors	31		dB
Rated heat output, cold climate:	9	10	kW
Rated heat output, warm climate:	8	8	kW
Annual energy consumption for space heating, cold climate	6292	9016	kWh
Annual electricity consumption for water heating, cold climate			kWh
Annual energy consumption for space heating, warm climate	1879	2371	kWh
Annual electricity consumption for water heating, warm climate			kWh
Seasonal space heating energy efficiency, cold climate:	138	106	%
Water heating energy efficiency, cold climate:			%
Seasonal space heating energy efficiency, warm climate:	224	177	%
Water heating energy efficiency, warm climate:			%
Sound power level LWA outdoors	52		dB

#### Data for package fiche

Controller class	CLASS VI		
Controller contribution to efficiency	4,0		%
Seasonal space heating energy efficiency of package, average climate:	156	130	%
Seasonal space heating energy efficiency class for package, average climate:	<b>A++</b>	<b>A++</b>	%
Seasonal space heating energy efficiency of package, cold climate:	142	110	%
Seasonal space heating energy efficiency of package, warm climate:	228	181	%

Model(s):		NIBE AMS 10-8 + SHB 10-12				<div>NIBE</div>			
Type of heat source/sink:		Air/water							
Low-temperature heat pump:		No							
Equipped with supplementary heater:		Yes							
Heat pump combination heater:		No							
Climate condition:		Average							
Temperature application:		Medium temperature (55 °C)							
Applied standards: EN 14825:2022, EN 12102-1:2022									
Rated heat output		Prated	7,0	kW	Seasonal space heating energy efficiency		$\eta_s$	126	%
Declared capacity for part load at outdoor temperature $T_j$					Declared coefficient of performance for part load at outdoor temperature $T_j$				
$T_j = -7\text{ °C}$	P <sub>dH</sub>	5,7	kW	$T_j = -7\text{ °C}$		COP <sub>d</sub>	2,01		
$T_j = +2\text{ °C}$	P <sub>dH</sub>	3,9	kW	$T_j = +2\text{ °C}$		COP <sub>d</sub>	3,20		
$T_j = +7\text{ °C}$	P <sub>dH</sub>	2,6	kW	$T_j = +7\text{ °C}$		COP <sub>d</sub>	4,21		
$T_j = +12\text{ °C}$	P <sub>dH</sub>	2,0	kW	$T_j = +12\text{ °C}$		COP <sub>d</sub>	5,18		
$T_j = \text{biv}$	P <sub>dH</sub>	5,7	kW	$T_j = \text{biv}$		COP <sub>d</sub>	2,01		
$T_j = \text{TOL}$	P <sub>dH</sub>	5,5	kW	$T_j = \text{TOL}$		COP <sub>d</sub>	1,78		
$T_j = -15\text{ °C}$ (if $\text{TOL} < -20\text{ °C}$ )	P <sub>dH</sub>		kW	$T_j = -15\text{ °C}$ (if $\text{TOL} < -20\text{ °C}$ )		COP <sub>d</sub>			
Bivalent temperature		T <sub>biv</sub>	-7	°C	Operation limit temperature		TOL	-10	°C
Cycling interval capacity for heating		P <sub>cycH</sub>		kW	Cycling interval efficiency		COP <sub>cyc</sub>		-
Degradation co-efficient		C <sub>dH</sub>	0,88	-	Heating water operating limit		WTOL	58	°C
Power consumption in modes other than active mode					Supplementary heater				
Off mode	P <sub>OFF</sub>	0,045	kW	Rated heat output		P <sub>sup</sub>	1,5	kW	
Thermostat-off mode	P <sub>TO</sub>	0,048	kW						
Standby mode	P <sub>SB</sub>	0,045	kW	Type of energy input		Electric			
Crankcase heater mode	P <sub>CK</sub>	0,000	kW						
Other items									
Capacity control		Variable			Rated air flow rate, outdoors			3000	m³/h
Sound power level, indoors/outdoors		L <sub>WA</sub>	31/52	dB	Rated water flow rate, indoor heat exchanger				m³/h
Annual energy consumption		Q <sub>HE</sub>	4486	kWh	Rated brine or water flow rate, outdoor heat exchanger				m³/h
For heat pump combination heater:									
Declared load profile					Water heating energy efficiency		$\eta_{wh}$		%
Daily electricity consumption	Q <sub>elec</sub>		kWh	Daily fuel consumption		Q <sub>fuel</sub>		kWh	
Annual electricity consumption	AEC		kWh	Annual fuel consumption		AFC		GJ	
Contact details		© NIBE Energy Systems - Box 14 - Hannabadsvägen 5 - 28521 Markaryd - Sweden							